



- A = Lagerung Kundenwelle Bearings for customer shaft
- K = Kundenseitige Anschlussmaße Required mating dimensions
- M = Meßpunkt Arbeitstemperatur Operating temperature measuring point
- H1 = Stiftleiste 12pol. 12-pin connector
- H2 = Gußdeckel Die-cast cover
- H3 = Verschlussschraube SW3 und 4 Anzugsmoment 5 +0,5Nm Locking screw SW3 and 4 torque 5 +0,5Nm
- H4 = Klemmschraube mit Innensechsrund X8 Anzugsmoment 1,1 ±0,1Nm Locking screw with hexalobular recesses X8 torque 1,1 ±0,1 Nm
- H5 = Drehrichtung der Welle für Ausgangssignale gemäß Schnittstellenbeschreibung Direction of shaft rotation for output signals as per the interface description

68A	43A	59	37D	Ø 12g7	Ø 12H7
WELLA1	KUPPA1	FLANA1	FOKAA1	D1 (E)	D2 (E)

Original drawing			ERN 1320		ID number:
Scale			ERN 1320		Change No. C045676-21
Format			Anschlussmaße / Mating Dimensions		Phase: Serie
Dimensions in mm	1:1	A2			Tolerierung nach DIN ISO 8015
					Allgemeintol. ISO 2768-mH ±6mm:±0,2
					General tol. ISO 2768-mH ±6mm:±0,2

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)