


Sicht auf die Stiftseite

Pin	Belegung	Farbe
1	A1+	grün
2	0V	weiß
3	A2+	rosa
4	V+	schwarz
5	nc	--
6	S1	orange
7	RI-	grau
8	S2	violett
9	A1-	gelb
10	0V Sensor	Brücke auf Pin 2
11	A2-	rot
12	V+ Sensor	Brücke auf Pin 4
13	SCL*	blau
14	RI+	braun
15	Test	naturfarben
Gehäuse	Schirm	Schirm

* Eingang, darf Kundenseitig nicht belegt werden



View on pins

Pin	Signal	Color
1	A1+	green
2	0V	white
3	A2+	pink
4	V+	black
5	nc	--
6	S1	orange
7	RI-	gray
8	S2	violet
9	A1-	yellow
10	0V sensor	connected to pin 2
11	A2-	red
12	V+ sensor	connected to pin 4
13	SCL*	blue
14	RI+	brown
15	Test	ecru
housing	shield	shield

* input, must not be used by customer

connection layout ~1Vss FQ		Pin Layout		Change No: C035200-5	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
RSF Elektronik www.rsf.at		Serie	Version	Revision	Sheet
		D1169918 - 00 - C - 01			Page 1/1
Document No					