



- A** = Lagerung Kundenwelle
Bearing for customer shaft
- K** = Kundenseitige Anschlussmaße
Required mating dimensions
- H1** = Nullposition Lage ±15°
Zero position ±15°
- H2** = SW3,0 (3x120°), Anzugsmoment 2,5 +0.5Nm
SW3,0 (3x120°), torque 2,5 +0.5Nm
- H3** = SW 3,0
Vor Inbetriebnahme Montagehilfe freidrehen!
SW 3,0
Turn fit-up aid before start up!
- H4** = Toleranzangabe beinhaltet Montagetoleranzen und
thermische Ausdehnung. Keine dynamische Bewegung zulässig.
Tolerance specification includes mounting tolerances and
thermal expansion. No dynamic motion permitted.
- H5** = Berührungsschutz nach EN 60529
Protection according to EN 60529
- H6** = Drehrichtung der Welle für Ausgangssignale
gemäß Schnittstellenbeschreibung
Direction of shaft rotation for output signals
due to interface specification

Datenschnittstelle Data interface SCHNA1	Kabel-Ø a Cable-DIA a
EnDat 02	6
EnDat 22	4,5
FANUC 05	4,5
Mitsubishi 02-4	4,5
Mitsubishi 03-4	4,5

Stoffschlüssige Losdrehesicherung (mittelfest, demontierbar)
Materialily bonding thread-locking fluid (medium strength, removable)

42C	Ø 38h7 E	Ø 38G7 E
42D	Ø 50h7 E	Ø 50G7 E
WELLA1	D1	D2

Original drawing		ECN 2xxx		ID number:
Scale	Format	ECN 2xxx		Change No. C161818-15
Dimensions in mm	1:1	Anschlussmaße / Mating Dimensions		Phase: Serie
				Tolerances as per ISO 8015
				General Tolerances ISO 2768:1989-mH ±0.2
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)				
HEIDENHAIN		Released	Version	Revision
DR. JOHANNES HEIDENHAIN GmbH		14.09.2023		
83301 Traunreut, Germany		D1182790-01-A-01		Sheet 1 of 1
		Document number		Page 1