



3r	Anschluss-Belegung	
	Elektrischer Anschluss	
	Geometrie Polbild (Steckseite)	
JH	Firmenname	JH
~1Vss	Ausgangssignal	~1Vss
..	Eingangssignal	..
..	Datenschnittstelle	..
..	Teilkreiszusatzspur	..
15 polig	Kundenseitige Steckerausführung	Ader
2	Versorgung 0V (Un)	weißgrün
10	Versorgung 0V (Sensorleitung)	weiß
4	Versorgung +V (Up)	braungrün
12	Versorgung +V (Sensorleitung)	blau
Gehäuse	Außenschirm	Schirm
1	Spannungssignal A+	braun
9	Spannungssignal A-	grün
3	Spannungssignal B+	grau
11	Spannungssignal B-	rosa
14	Spannungssignal R+	rot
7	Spannungssignal R-	schwarz
15	Serielle Schnittstelle serial Data	gelb
13	Serielle Schnittstelle Takt	violett
5, 6, 8	Freie Adern und Pins	

3r	Pin configuration	
	Electrical connection	
	Geometry of pole pattern (plug side)	
JH	company name	JH
~1Vpp	Output signal	~1Vpp
..	Input signal	..
..	Data interface	..
..	Additional circular scale track	..
15-pin	Customer's connection version	Wire
2	Supply 0V (Un)	white and green
10	Supply 0V (sensor line)	white
4	Supply +V (Up)	brown and green
12	Supply +V (sensor line)	blue
Housing	External shield	Shield
1	Voltage signal A+	brown
9	Voltage signal A-	green
3	Voltage signal B+	grey
11	Voltage signal B-	pink
14	Voltage signal R+	red
7	Voltage signal R-	black
15	Serial interface for serial data	yellow
13	Serial interface for clock	violet
5, 6, 8	Free wires and pins	

Connection layout 3r 16S15 ~1Vpp JH		Pin Layout		Change No: C039509-00	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.					
HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Serie	Version	Revision	Sheet
		D1197355 - 00 - A - 01			Page 1/1
Document No					