


Sicht auf die Stiftseite



View on pins

Pin	Belegung	Farbe
1	A2-	rot
2	A1-	gelb
3	RI-	grau
4	V+	schwarz
5	V+ Sensor	Brücke auf Pin 4
6	A2+	rosa
7	A1+	grün
8	RI+	braun
9	0V	weiß
10	0V Sensor	Brücke auf Pin 9
11	SCL*	blau
12	nc	--
13	Test	naturfarben
14	nc	--
15	nc	--
Gehäuse	Schirm	Schirm

* Eingang, darf Kundenseitig nicht belegt werden

Pin	Signal	Color
1	A2-	red
2	A1-	yellow
3	RI-	gray
4	V+	black
5	V+ sensor	connected to pin 4
6	A2+	pink
7	A1+	green
8	RI+	brown
9	0V	white
10	0V sensor	connected to pin 9
11	SCL*	blue
12	nc	--
13	test	ecru
14	nc	--
15	nc	--
housing	shield	shield

* input, must not be used by customer

connection layout ~1Vss 0s		Pin Layout		Change No. C033972-20	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
RSF Elektronik www.rsfs.at		Serie	Version	Revision	Sheet
		D1217593 - 00 - B - 01			Page 1/1
Document No					