


Sicht auf die Stiftseite



View on pins

Pin	Belegung	Farbe
1	Test	naturfarben
2	nc	--
3	SCL*	blau
4	V+	schwarz
5	0V	weiß
6	A2-	rot
7	A1-	gelb
8	RI-	grau
9	nc	--
10	nc	--
11	nc	--
12	0V	Brücke auf Pin 5
13	A2+	rosa
14	A1+	grün
15	RI+	braun
Gehäuse	Schirm	Schirm

* Eingang, darf Kundenseitig nicht belegt werden

Pin	Signal	Color
1	test	ecru
2	nc	--
3	SCL*	blue
4	V+	black
5	0V	white
6	A2-	red
7	A1-	yellow
8	RI-	gray
9	nc	--
10	nc	--
11	nc	--
12	0V	connected to pin 5
13	A2+	pink
14	A1+	green
15	RI+	brown
housing	shield	shield

* input, must not be used by customer

connection layout ~1Vss 2i		Pin Layout		Change No: C043164-74	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
RSF Elektronik www.rsfsf.at		Serie	Version	Revision	Sheet
		D1231990 - 00 - B - 01			Page
		Document No			1/1