





5u	<b>Anschluss-Belegung</b>	
	<b>Elektrischer Anschluss</b>	
	<b>Geometrie Polbild (Steckseite)</b>	
JH	<b>Firmenname</b>	JH
..	<b>Ausgangssignal</b>	..
..	<b>Eingangssignal</b>	..
..	<b>Datenschnittstelle</b>	..
..	<b>Teilkreiszusatzspur</b>	..
4 polig	Kundenseitige Steckerausführung	Ader
1a	Zusätzliche Signale Temperatur +	braun
1b	Zusätzliche Signale Temperatur -	grün
2a	Freie Adern und Pins	
2b	Freie Adern und Pins	

5u	<b>Pin configuration</b>	
	<b>Electrical connection</b>	
	<b>Geometry of pole pattern (plug side)</b>	
JH	<b>company name</b>	JH
..	<b>Output signal</b>	..
..	<b>Input signal</b>	..
..	<b>Data interface</b>	..
..	<b>Additional circular scale track</b>	..
4-pin	Customer's connection version	wire
1a	Additional signals temperature +	brown
1b	Additional signals temperature -	green
2a	Free wires and pins	
2b	Free wires and pins	

Connection layout 5u 90B04 .. .. .. JH		Pin Layout		Change No: C087027-3	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
<b>HEIDENHAIN</b> DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Serie	Version	Revision	Sheet
		<b>D1272645 - 00 - B - 05</b>			Page 1/1
Document No					