



Toleranztabelle	
L	T
<= 250mm	± 5mm
< 1000mm	+ 10mm

TE Connectivity Ltd
 61.253.11 (Serie 723 Einzelkontakt) oder
 61.083.11 (Serie 623 Einzelkontakt) oder
 61.171.80 (Serie 623 Bandkontakt)

⊙ A	Signaladern	
	Biegeradius min. einmalig / min. bend radius for rigid configuration	5mm
	Aderdurchmesser	0,81mm
	Querschnitt / Cross section	0,15mm ² / AWG26
	Durchmesser / Diameter	1,8mm
	Arbeitsspannung	50V
	Prüfspannung	3,4kV
	Temperaturbereich	-65°C / +150°C

max. Kabellänge (L): siehe Techn. Daten des Gerätetyps
 For max. cable length (L): See Specifications of the encoder model

			IDnumber:
			Change No. C187996-10 Phase: Serie
	Original drawing Scale Format	AGK E30 90B012 --> 22S02	Tolerances as per ISO 8015
Dimensions in mm	1:1 A3	Anschlussmaße	General Tolerances ISO 2768:1989-mH ±0,2
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)			
HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Released 11.11.2025	Version Revision Sheet D 1277276-00-C-09 1 of 1
		Document number	