



Toleranztabelle	
L / L1	T
≤ 250mm	± 5mm
< 1000mm	+ 10mm

(B) **Temperatursensor / Temperature sensor**  
 Biegeradius min. / min. bend radius 3mm  
 Aderdurchmesser 0,81mm  
 Querschnitt / Cross section 0,15mm<sup>2</sup> / AWG26  
 Durchmesser / Diameter 2,2mm  
 Arbeitsspannung 50V  
 Prüfspannung 3,4kV  
 Temperaturbereich -55°C / +135°C

(A) **Signaladern**  
 Biegeradius min. einmalig / min bend radius für rigid configuration 5mm  
 Aderdurchmesser 0,81mm  
 Querschnitt / Cross section 0,15mm<sup>2</sup> / AWG26  
 Durchmesser / Diameter 1,8mm  
 Arbeitsspannung 50V  
 Prüfspannung 3,4kV  
 Temperaturbereich -65°C / +150°C

max. Kabellänge (L): siehe Techn. Daten des Gerätetyps  
 For max. cable length (L): See Specifications of the encoder model

			IDnumber:
			Change No. C165519-10 Phase: Serie
	Original drawing Scale   Format	AGK E30 3VB015 --> 01 (01)	Tolerances as per ISO 8015
Dimensions in mm	1:1   A3	Anschlussmaße	General Tolerances ISO 2768:1989-mH ±0,2
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. ( ISO 16016 )			
<b>HEIDENHAIN</b> DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Released 07.12.2023	Version   Revision   Sheet D 1277276-02-B-02 1 of 1
		Document number	