



Harwin
M80-8080205

Toleranztabelle	
L	T
<= 250mm	± 5mm
< 1000mm	+ 10mm
<= 3000mm	+ 30mm
> 3000mm	+ 1%

Temperatursensor / Temperature sensor
 Biegeradius min. einmalig / min. bend radius für rigid configuration 5mm
 Aderdurchmesser 0,81mm
 Querschnitt / Cross section 0,15mm² / AWG26
 Durchmesser / Diameter 2,2mm
 Arbeitsspannung 50V
 Prüfspannung 3,4kV
 Temperaturbereich (Adern im Schrumpfschlauch) -55°C / +150°C
 (komplette Baugruppe) -40°C / +120°C

max. Kabellänge (L): siehe Techn. Daten des Gerätetyps
 For max. cable length (L): See Specifications of the encoder model

			IDnumber:
			Change No. C165519-10 Phase: Serie
	Original drawing Scale	Format	Tolerances as per ISO 8015
Dimensions in mm	1:1	A4	General Tolerances ISO 2768:1989-mH ±6mm: ± 0,2
AGK Sensor 90B004 --> AGS02			
Anschlussmaße			

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)

HEIDENHAIN
 DR.JOHANNES HEIDENHAIN GmbH
 83301 Traunreut, Germany

Released

07.12.2023

Version Revision Sheet

D 1277276-02-C-07

1 of 1

Document number