



- 1 = Tightening torque of the M4 - 8.8 cylinder head screw:  $2,5 \text{ Nm} \pm 0,13 \text{ Nm}$
- 2 = Mark of  $0^\circ$  position  $\pm 5^\circ$
- 3 = Direction of rotation for ascending position values
- 4 = LED position
- 5 = Permitted for shaft clamping
- 6 = Blocking area for flex PCB

Original drawing		ID number:	
Scale	Format	Change No.	C112975-15
Dimensions in mm	1:1 A3	Phase:	Serie
MRS 2281 MRS Anschlussmaße / Mating Dimensions		Tolerierung nach DIN ISO 8015 Tolerances as per DIN ISO 8015	
		Allgemeintol. ISO 2768-mH $\leq 6\text{mm}$ : $\pm 0,2$ General tol. ISO 2768-mH $\leq 6\text{mm}$ : $\pm 0,2$	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. ( ISO 16016 )			
<b>HEIDENHAIN</b> DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Version	Revision
		Sheet	Page
D1292320-00-D-01		1 of 1	
Document number			