



Rechtsdrehend




Linksdrehend




Sicht auf die Steckseite

Pin	Belegung	Farbe
1	T2 invers	rot
2	V+ Sensor	orange
3	RI	braun
4	RI invers	grau
5	T1	grün
6	T1 invers	gelb
7	US invers	blau
8	T2	rosa
9	nc	--
10	0V	weiß
11	0V Sensor	violett
12	V+	schwarz
Gehäuse	Schirm	Schirm

Pin rotation CW



Pin rotation CCW



View on connecting side

Pin	Signal	Color
1	T2 inverse	red
2	V+ sensor	orange
3	RI	brown
4	RI inverse	gray
5	T1	green
6	T1 inverse	yellow
7	US inverse	blue
8	T2	pink
9	nc	--
10	0V	white
11	0V sensor	violet
12	V+	black
housing	shield	shield

connection layout TTL Fz

Pin Layout

Change No: C130195-06

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)

RSF Elektronik
www.rsrf.at

Serie	Version	Revision	Sheet	Page
D1358026 - 00 - A - 01				1/1
Document No				