


Sicht auf die Stiftseite



View on pins

Pin	Belegung	Farbe
1	T1	grün
2	0V	weiß
3	T2	blau
4	V+	braun
5	nc	--
6	nc	--
7	RI invers	rosa
8	nc	--
9	T1 invers	gelb
10	0V Sensor	Brücke auf Pin 2
11	T2 invers	rot
12	V+ Sensor	Brücke auf Pin 4
13	US invers	violett
14	RI	grau
15	Test	schwarz
Gehäuse	Schirm	Schirm

Pin	Signal	Color
1	T1	green
2	0V	white
3	T2	blue
4	V+	brown
5	nc	--
6	nc	--
7	RI inverse	pink
8	nc	--
9	T1 inverse	yellow
10	0V sensor	connected to pin 2
11	T2 inverse	red
12	V+ sensor	connected to pin 4
13	US inverse	violet
14	RI	grey
15	Test	black
housing	shield	shield

connection layout TTL Ig		Pin Layout		Change No: C150228-01	
<small>The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)</small>					
RSF Elektronik		Serie	Version	Revision	Sheet
www.rsrf.at		D1394297 - 00 - A - 01			Page 1/1
Document No					