



04	Anschluss-Belegung	
	Elektrischer Anschluss	
	Geometrie Polbild (Steckseite)	
~11µAss	Ausgangssignal	~11µAss
..	Eingangssignal	..
..	Datenschnittstelle	..
..	Teilkreiszusatzspur	..
9 polig	Kundenseitige Steckerausführung	Litzen
4	Versorgung 0V (Un)	weiß
3	Versorgung +V (Up)	braun
Gehäuse	Außenschirm	Schirm
9	Innenschirm (0V)	weißbraun
1	Stromsignal (4x90°) 0° +	grün
2	Stromsignal (4x90°) 0° -	gelb
5	Stromsignal (4x90°) 90° +	blau
6	Stromsignal (4x90°) 90° -	rot
7	Stromsignal (4x90°) RI +	grau
8	Stromsignal (4x90°) RI -	rosa
	Freie Litzen und Pins	braungrün
0035	Ergänzungen	0035

0035 = Litze braungrün nur bei Kabeldurchmesser 4,5mm vorhanden

04	Pin configuration	
	Electrical connection	
	Geometry of pole pattern (plug side)	
~11µApp	Output signal	~11µAss
..	Input signal	..
..	Data interface	..
..	Additional circular-scale track	..
9-pin	Customer's connection version	litzes
4	Supply 0 V (Un)	white
3	Supply +V (Up)	brown
housing	External shield	shield
9	Internal shield (0 V)	whitebrown
1	Current signal (4x90°) 0° +	green
2	Current signal (4x90°) 0° -	yellow
5	Current signal (4x90°) 90° +	blue
6	Current signal (4x90°) 90° -	red
7	Current signal (4x90°) RI +	grey
8	Current signal (4x90°) RI -	pink
	Free wires and pins	browngreen
0035	Additions	0035

0035 = Litz brown and green only available for cable diameter 4.5mm

connection layout 04 02S09 ~11µA	Pin Layout	Release No:	90119
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.			
HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany	Version	Revision	Sheet
	D295051 - 00 - A - 02		
	Page	1/1	
	Document No		