



24	Anschluss-Belegung	
	Elektr. Anschluss	
	Geometrie Polbild (Steckseite)	
Taster	Ausgangssignal	Taster
..	Eingangssignal	..
..	Datenschnittstelle	..
..	Teilkreiszusatzspur	..
7 polig	Kundenseitige Steckerausführung	Litzen
1	Versorgung 0V (Un)	weiß
2	Versorgung +V (Up)	braun
Gehäuse	Außenschirm	Schirm
5+6	Zusätzliche Signale Brücken zwischen Pin	
3	Taster Signale Schaltsignal	grün
4	Taster Signale Schaltsignal invers	gelb
7	Freie Litzen und Pins	

24	Pin configuration	
	Electrical connection	
	Geometry of pole pattern (plug side)	
Probe	Output signal	Taster
..	Input signal	..
..	Data interface	..
..	Additional circular-scale track	..
7 pin	Customer's connection version	litzes
1	Supply 0V (Un)	white
2	Supply +V (Up)	browm
housing	External shield	shield
5+6	Addit. Signals of bridges betw. pins	
3	Probe signals, switching signal	green
4	Probe signals, switch signal, inv.	yellow
7	Free wires and pins	

connection layout 24 02S07 Taster				Pin Layout		Change No: C47292-10			
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.									
HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany				Serie		Version	Revision	Sheet	Page 1/1
				D295780		- 00	- A	- 02	
				Document No					