



30	Anschluss-Belegung
	Elektrischer Anschluss
	Geometrie Polbild (Steckseite)
JH	Firmenname
HTL	Ausgangssignal
..	Eingangssignal
..	Datenschnittstelle
..	Teilkreiszusatzspur
12 polig	Kundenseitige Steckerausführung
1a	Versorgung 0V (Un)
1b	Versorgung 0V (Sensorleitung)
2a	Versorgung +V (Up)
2b	Versorgung +V (Sensorleitung)
Flansch, Kappe	Außenschirm
6b	Rechteck-Signal Ua1
6a	Rechteck-Signal Ua1 invers
5b	Rechteck-Signal Ua2
5a	Rechteck-Signal Ua2 invers
4b	Rechteck-Signal Ua0
4a	Rechteck-Signal Ua0 invers
3a	Rechteck-Signal UaS invers
3b	Freie Adern und Pins

30	Pin configuration
	Electrical connection
	Geometry of pole pattern (plug side)
JH	Company name
HTL	Output signal
..	Input signal
..	Data interface
..	Additional circular scale track
12-pin	Customer's connection version
1a	Supply 0V (Un)
1b	Supply 0V (sensor line)
2a	Supply +V (Up)
2b	Supply +V (sensor line)
Flange, housing	External shield
6b	Square-wave signal Ua1
6a	Square-wave signal Ua1 inverse
5b	Square-wave signal Ua2
5a	Square-wave signal Ua2 inverse
4b	Square-wave signal Ua0
4a	Square-wave signal Ua0 inverse
3a	Square-wave signal UaS inverse
3b	Free wires and pins

connection layout 30 62S12 HTL	Pin Layout	Change No. C152702-20
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)		
HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany	Serie D297243 - 00 - B - 05	Version Revision Sheet Page 1/1
Document No		