





<b>0V</b>	<b>Anschluss-Belegung</b>	
	<b>Elektr. Anschluss</b>	
	<b>Geometrie Polbild (Steckseite)</b>	
<b>JH</b>	<b>Firmenname</b>	
<b>TTL</b>	<b>Ausgangssignal</b>	<b>TTL</b>
..	<b>Eingangssignal</b>	..
..	<b>Datenschnittstelle</b>	..
..	<b>Teilkreiszusatzspur</b>	..
15 polig	Kundenseitige Steckerausführung	Adern
2	Versorgung 0V (Un)	weißgrün
10	Versorgung 0V (Fühlleitung)	weiß
4	Versorgung +V (Up)	braungrün
12	Versorgung +V (Fühlleitung)	blau
Im Messgerät	Versorgung verbunden mit Fühlleitung	Im Messgerät
Gehäuse	Außenschirm	Schirm
1	Rechteck-Signal Ua1	braun
9	Rechteck-Signal Ua1 invers	grün
3	Rechteck-Signal Ua2	grau
11	Rechteck-Signal Ua2 invers	rosa
14	Rechteck-Signal Ua0	rot
7	Rechteck-Signal Ua0 invers	schwarz
13	Rechteck-Signal UaS invers	violett
15	Rechteck-Signal PWT Testimpuls	gelb
5	Freie Litzen und Pins	
6	Freie Litzen und Pins	
8	Freie Litzen und Pins	
0040	Ergänzungen	

0040 = Existenz und Funktion von UaS- und PWT Testimpuls siehe Techn. Daten

<b>0V</b>	<b>Pin configuration</b>	
	<b>Electrical connection</b>	
	<b>Geometry of pole pattern (plug side)</b>	
<b>JH</b>	<b>Company name</b>	
<b>TTL</b>	<b>Output signal</b>	<b>TTL</b>
..	<b>Input signal</b>	..
..	<b>Data interface</b>	..
..	<b>Additional circular-scale track</b>	..
15-pin	Customer's connection version	Wire
2	Supply 0V (Un)	white and green
10	Supply 0 V (sensor line)	white
4	Supply +V (Up)	brown and green
12	Supply +V (sensor line)	blue
In the encoder	Supply connected with sensor line	In the encoder
Housing	External shield	Shield
1	Square-wave signal Ua1	brown
9	Square-wave signal Ua1 inverse	green
3	Square-wave signal Ua2	grey
11	Square-wave signal Ua2 inverse	pink
14	Square-wave signal Ua0	red
7	Square-wave signal Ua0 inverse	black
13	Square-wave signal UaS inverse	violet
15	Square-wave signal PWT test pulse	yellow
5	Free wires and pins	
6	Free wires and pins	
8	Free wires and pins	
0040	Additions	0040

0040 = Existence and function of UaS- and PWT test pulse, see specifications

Connection layout 0V 16S15 TTL .. .. .		Pin Layout		Change No: R1150	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
<b>HEIDENHAIN</b> DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Serie	Version	Revision	Sheet
		<b>D330978 - 00 - B - 03</b>			Page
		Document No			1/1