



- A** = Lagerung Kundenwelle
Bearing of mating shaft
- K** = Kundenseitige Anschlussmaße
Required mating dimensions
- M1** = Messpunkt Arbeitstemperatur
Measuring point for operating temperature
- M2** = Messpunkt Vibration
Measuring point for vibration
- H1** = Klemmschraube mit Innensechsrund X8
Anzugsmoment: 1,1 ±0,1 Nm
Locking screw with hexalobular recesses X8
Tightening torque: 1.1 ±0.1 Nm
- H2** = Ausgleich von Montagetoleranzen und thermischer Ausdehnung, keine dynamische Bewegung
Compensation of mounting tolerances and thermal expansion, no dynamic motion
- H3** = Drehrichtung der Welle für Ausgangssignale gemäß Schnittstellenbeschreibung
Direction of shaft rotation according to interface description
- H4** = Befestigung Statorkupplung z. B. 4x ISO 4762 - 8.8 - MKL M3x10
Anzugsmoment: 1 ±0,06Nm
Fastening Stator coupling e. g. 4x ISO 4762 - 8.8 - MKL M3x10
Tightening torque: 1 ±0.06Nm

68E	φ 15H7	φ 15g7	14
68B	φ 14H7	φ 14g7	14
68A	φ 12H7	φ 12g7	14
68C	φ 10H7	φ 10g7	14
68D	φ 9,52H7	φ 9,52g7	14
68F	φ 8H7	φ 8g7	14
WELLA1	D	d	KUPPA1

KABEA2	A
01	φ 4,5
02	φ 6

Original drawing		ERN/ECN/EQN 4xx		ID number:
Scale		ERN/ECN/EQN 4xx		Change No. C172391-15
Format		Anschlussmaße / Mating Dimensions		Phase: Serie
Dimensions in mm	1:1	A2		Tolerances as per ISO 8015
				General Tolerances ISO 2768:1989-mH ±0,2
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)				
HEIDENHAIN		Released	Version	Revision
DR. JOHANNES HEIDENHAIN GmbH		06.10.2025		
83301 Traunreut, Germany		D 372796-13-A-01		Sheet 1 of 1
		Document number		Page 1 of 1