



- A** = Lagerung Kundenwelle  
Bearing for customer shaft
- K** = Kundenseitige Anschlussmaße  
Required mating dimensions
- M** = Messpunkt Arbeitstemperatur  
Operating temperature measuring point
- H1** = Referenzmarken-Lage ±20°  
Reference mark position ±20°
- H2** = Maximal zulässige Bewegung  
der Motorwelle  
Max. tolerable movement  
of the customer shaft
- H3** = 2x Schraube Klemmring. Anzugsmoment 0,6±0,1Nm  
2x screw clamping ring. Torque 0,6±0,1Nm SW 1.5

							α = 10°	α = 2°		
50E	14A	49A	∅ 6 g7 (E)	(∅ 6)	..	Z1				
50C	14A	49A	∅ 4 g7 (E)	(∅ 4)	..	Z1				
50E	14A	49A	∅ 6 g7 (E)	(∅ 6)	..	Z1				
50F	14A	49A	∅ 6,35 g7 (E)	(∅ 6,35)	..	Z1				
							ID number:			
WELLA1	KUPPA1	FOKAA1	D1	D2	ZUTEA1	ZUTEA1	Release number: N2944			
			ERN 10xx		WELLA1=50x KUPPA1=14A		Tolerierung nach DIN ISO 8015		Tolerances as per DIN ISO 8015	
					Anschlussmaße		Allgemeintol. ISO 2768-mH ∓6mm:±0,2		General tol. ISO 2768-mH ∓6mm:±0,2	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)										
<b>HEIDENHAIN</b>							Version		Revision	
DR. JOHANNES HEIDENHAIN GmbH							Sheet		Page	
83301 Traunreut, Germany							1		1	
							D 520910-01-A-01		Document number	