





C4	Anschluss-Belegung	
	Elektr. Anschluss	
	Geometrie Polbild (Steckseite)	
..	Ausgangssignal	..
..	Eingangssignal	..
Fanuc	Datenschnittstelle	Fanuc
..	Teilkreiszusatzspur	..
8 polig	Kundenseitige Steckerausführung	Litzen
5	Versorgung 0V (Un)	weißgrün
1	Versorgung 0V (Fühlleitung)	weiß
8	Versorgung +V (Up)	braungrün
2	Versorgung +V (Fühlleitung)	blau
Im Messgerät	Versorgung verbunden mit Fühlleitung	Im Messgerät
Gehäuse	Außenschirm	Schirm
3	Serielle Schnittstelle serial Data	grau
4	Serielle Schnittstelle serial Data inver	rosa
7	Serielle Schnittstelle Request Frame	violett
6	Serielle Schnittstelle Request Frame inv	gelb

C4	Connection layout	
	Electrical connection	
	Geometry of pole pattern (plug side)	
..	Output signal	..
..	Input signal	..
Fanuc	Data interface	Fanuc
..	Additional circular-scale track	..
8-pin	Customer's connection version	litzes
5	Supply 0 V (Un)	whitegreen
1	Supply 0 V sensor line	white
8	Supply +V (Up)	browngreen
2	Supply +V (sensor line)	blue
in encoder	Supply connected with sensor line	in encoder
housing	External shield	shield
3	Serial interface for serial data	grey
4	Ser. interface for ser. data, inv.	pink
7	Serial interface Request Frame	violet
6	Serial interface Request Frame, inv.	yellow

Connection layout C4 5XS08 .. Fanuc		Pin Layout		Change No: R6	R6160
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.					
HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Serie	Version	Revision	Sheet
		D532351	- 00	- B	- 19
		Document No			Page 1/1