



- A** = Lagerung Kundenwelle
Bearing of mating shaft
- K** = Kundenseitige Anschlussmaße
Required mating dimensions
- M1** = Messpunkt Arbeitstemperatur
Measuring point for operating temperature
- M2** = Messpunkt Vibration
Measuring point for vibration
- H1** = Klemmschraube mit Innensechsrund X8
Anzugsmoment 1,1 ±0,1 Nm
Locking screw with hexalobular recesses X8
Tightening torque 1.1 ±0.1 Nm
- H2** = Ausgleich von Montagetoleranzen und thermischer Ausdehnung, keine dynamische Bewegung
Compensation of mounting tolerances and thermal expansion, no dynamic motion
- H3** = Befestigung Statorkupplung z.B. 4x ISO 4762 8.8 MKL M3x10
Anzugsmoment: 1 ±0,06Nm
Fastening stator coupling e. g. 4x ISO 4762 8.8 MKL M3x10
Tightening torque: 1 ±0.06Nm
- H4** = Drehrichtung der Welle für steigende Positionswerte
Direction of shaft rotation for ascending position values

68B	φ 14H7	φ 14g7	14
68A	φ 12H7	φ 12g7	14
68C	φ 10H7	φ 10g7	14
68D	φ 9,52H7	φ 9,52g7	14
68F	φ 8H7	φ 8g7	14
WELLA1	D	d	KUPPA1

Original drawing		ECN/EQN 4xx		ID number:
Scale	Format	ECN/EQN 4xx		Change No. C172391-15
Dimensions in mm	1:1	A2	Anschlussmaße / Mating Dimensions	Phase: Serie
Tolerances as per ISO 8015				General Tolerances ISO 2768:1989-mH ±0.2
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)				
HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Released 06.10.2025	Version Revision Sheet Page D 541103-07-B-01 Document number	1 of 1

886 200 A2