



			L
Generation 3.2	ROC / ROQ	2048 Striche / Lines	42,7±0,5
Generation 3.1	ROC / ROQ	2048 Striche / Lines	43,2±0,5

- A** = Lagerung Geber                      Bearings for encoder
- B** = Befestigungsgewinde              Threaded mounting hole
- M** = Messpunkt Arbeitstemperatur      Operation temperature measuring point
- H1** = Umstellung der Gewindetiefe von 5mm auf 9mm ist in Umsetzung seit November 2011      Change of thread depth from 5mm to 9mm is currently being implemented since november 2011

73A	01C	∅ 58	M4 - 9+1 tief/depth (M4 - 5 tief/depth)	
73A	01B	∅ 55	M5 - 9+1 tief/depth (M5 - 5 tief/depth)	
WELLA1	FLANA1	D	a	ID number:
				Release number: R8678
				Tolerierung nach DIN ISO 8015
				Allgemeintol. ISO 2768-mH ∓6mm:±0,2 General tol. ISO 2768-mH ∓6mm:±0,2
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)				
<b>HEIDENHAIN</b> DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany				Version   Revision   Sheet   Page
D 541104-04 - A-01				1 of 1
Document number				