



| Schnittstelle Interface | Kabel-Ø a Cable-DIA a |
|----------------------------|--------------------------|
| EnDat 02 | 6 |
| EnDat 22 | 4,5 |
| FANUC 02 | 4,5 |
| Mitsubishi 02 - 04 | 4,5 |

- A** = Lagerung Kundenwelle
Bearing for customer shaft
- K** = Kundenseitige Anschlussmaße
Required mating dimensions
- M** = Messpunkt Arbeitstemperatur
Operating temperature measuring point
- H1** = Nullposition Lage ±15°
Zero position ±15°
- H2** = SW3,0 (3x120°), Anzugsmoment 2,5 +0.5Nm
SW3,0 (3x120°), torque 2,5 +0.5Nm
- H3** = SW 3,0
Vor Inbetriebnahme Montagehilfe freidrehen!
SW 3,0
Turn fit-up aid before start up!
- H4** = Maximal zulässige Bewegung der Motorwelle
Max. tolerable movement of the customer shaft
- H5** = Berührschutz nach EN 60529
Protection according to EN 60529

| | | |
|--------|----------|----------|
| 42C | Ø 38h7 E | Ø 38G7 E |
| 42D | Ø 50h7 E | Ø 50G7 E |
| WELLA1 | D1 | D2 |

| | | | | | | |
|---|-----|-----------------------------------|--|------------|--|---|
| Original drawing | | ECN 225/223x | | WELLA1=42x | | ID number: - |
| Scale | | ECN 225/223x | | WELLA1=42x | | Change No. C020812-10 |
| Format | | Anschlussmaße / Mating Dimensions | | | | Phase: Serie |
| Dimensions in mm | 1:1 | A2 | | | | Tolerierung nach DIN ISO 8015 Tolerances as per DIN ISO 8015 |
| | | | | | | Allgemeintol. ISO 2768-mH ±6mm:±0,2 General tol. ISO 2768-mH ±6mm:±0,2 |
| The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016) | | | | | | |
| HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany | | | | | | Version Revision Sheet Page 1 1 of 1 |
| D 572641-02 - B-01 | | | | | | Document number |