



- A** = Lagerung Kundenwelle Bearings for customer shaft
- K** = Kundenseitige Anschlußmaße Required mating dimensions
- M** = Messpunkt Arbeitstemperatur Operating temperature measuring point
- H1** = Selbstsichernde Schraube M5 x 50
DIN 6912 - SW 4
Anzugsmoment 5 +0,5 Nm Self - locking - screw M5 x 50
DIN 6912 - SW 4
torque 5 +0,5 Nm
- H2** = Verschlussschraube SW 3 und 4
Anzugsmoment 5 +0.5 Nm locking screw SW 3 and 4
torque 5 +0.5 Nm
- H3** = Abdrückgewinde M10 back - off thread M10
- H4** = Abdrückgewinde M6 back - off thread M6
- H5** = Ausgleich von Montagetoleranzen
und thermischer Ausdehnung,
keine dynamische Bewegung Compensation of mounting
tolerances and thermal expansion,
no dynamic motion

65B	04
WELLA1	KUPPA1

Original drawing		ERN 4x1		ID number:
Scale	Format	ERN 4x1		Change No. C151346-05
Dimensions in mm	1:1 A2	Anschlussmaße / Mating Dimensions		Phase: Serie
				Tolerances as per ISO 8015
				General Tolerances ISO 2768:1989-mH ±0.2

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of a patent, utility model or design. (ISO 16016)

HEIDENHAIN		Released	Version	Revision	Sheet	Page
DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		30.10.2023			1	1
D 595653-02 - A-01					Document number	