

Biegeradius min. dauernd Min. bend radius for flexing	--
Biegeradius min. einmalig Min. bend radius for rigid configuration	18mm
Schleppkettenradius min. Min. drag chain radius	--

max. Kabellänge (L): siehe Techn. Daten des Gerätetyps
For max. cable length (L): See Specifications of the encoder model

kundenseitige Anschlussmaße siehe D1140890 Bl.01 / D1218918 Bl.02
required mating dimensions see D1140890 Bl.01 / D1218918 Bl.02

Lochkreis-Durchmesser 28mm
bolt-hole circle diameter 28mm

				IDnumber:
				Change No. C056908-18 Phase: Serie
	Original drawing Scale	Format	AGK JAE --> Winkeldose M23 (68Sxx)	Tolerierung nach DIN ISO 8015 Tolerances as per DIN ISO 8015
Dimensions in mm	1:1	A3	Anschlussmaße	Allgemeintoleranzen ISO 2768-mH ≤6mm: +- 0,2 General tolerances ISO 2768-mH ≤6mm: +- 0,2

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)

HEIDENHAIN
DR.JOHANNES HEIDENHAIN GmbH
83301 Traunreut, Germany

Version	Revision	Sheet
D 652661	-03-	A -41

Document number

1 of 1

886 200 A3