



- A** = Lagerung Kundenseite
Bearing for customer shaft
- K** = Kundenseitige Anschlussmaße
Required mating dimensions
- M** = Meßpunkt Arbeitstemperatur
Operating temperature measuring point
- H1** = Nullposition ±15°
Zero position ±15°
- H2** = Klemmelement SW3 (3x120°), Md= 2,5 +0,5Nm
Locking element SW3 (3x120°), Md= 2,5 +0,5Nm
- H3** = M12 Stecker-Codierung
M12 Pin-Code
- H4** = Ausgleich von Montagetoleranzen und thermischer Ausdehnung,
keine dynamische Bewegung
Compensation of mounting tolerances and thermal expansion,
no dynamic motion
- H5** = Berührungsschutz nach EN 60529
Protection according to EN 60529

Ø 50h7	56	58,5	55	41,5	42D	32C	30A	5XS08
Ø 38h7	56	58,5	55	41,5	42C			
Ø 25h7	41	43,5	40	26,5	42B	33C		
Ø 20h7	41	43,5	40	26,5	42A			
D	L1	L2	L3	L4	WELLA1	FLANA1	KUPPA1	ANELA1

Original drawing		ECN 125		ID number:
Scale	Format	ECN 125		Change No. C006799-15
Dimensions in mm	1:1	Anschlussmaße / Mounting Dimensions		Phase: Serie
				Tolerierung nach DIN ISO 8015
				Tolerances as per DIN ISO 8015
				Allgemeintol. ISO 2768-mH ±0,2
				General tol. ISO 2768-mH ±0,2

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)